

# FLAMAN

# Avonlea




## X-TENDED REACH GRAIN CARTS

WIDE TOP 22 SERIES • STANDARD TOP 12 SERIES

22 Series Models: 1122, 1222, 1522 → Capacities: 1130bu to 1475bu

### Standard Features:

- Bullet Auger 
- Doubled flighting on the intake end of the auger increases unload speed
- Lock N- Load safety valve
- Locks auger while PTO is turning
- X-Tended reach front fold auger
- 100% visibility during unfolding/folding of auger
- Wide top design
- 2' closer to the combine
- Side Shooter auger spout
- Graphite coated interior for easy cleanout

### Optional Features:

- 5 Point scale system - c/w standard monitor
- Optional autolog kit or wireless Ifarm app for mobile device
- Auto gate shut off kit
  - will shut gate at pre-determined weight (autolog monitor only)
- Hydraulic drive kit
- Choice of Large Flotation Tires, Walking Tandem Dual Wheels or Storm Tracker Track System
- Red, green, blue, yellow, tan, black or custom paint
- Moisture Sensor Option



12 Series Models: 812, 1012, 1112, 1312, 1412 → Capacities: 875bu to 1400bu

All features are the same as the 20 series with the exception of the wide top design.

Model 812 - Single wheels or LT Tracks, conventional 18" auger

Models 1012 & up - Single wheel, walking tandem dual, or tracks, bullet auger

## New Available Paint Colors!

J&M now has new paint colors for your grain cart! Choose from red, green, yellow, blue, tan, black, or custom!




## FEATURES

### Side-Shooter Flow Control Spout

Allows you to correct the position of the spout on "to close" or "to far" approaches. It throws grain directly towards the semi-trailer, not at an angle, maximizing the side reach and throw for a complete fill everytime!

### XTended Reach Auger

Allows you to simply look out the side window of your tractor cab when unloading. 100% visibility all the time! Up to 4' more reach than other augers!



### Storm Tracker Tracks

The innovative Storm Tracker track system is built to last and boasts an array of unique features. As opposed to hydraulic tension, StormTracker uses an airbag system.

**Wide Top Design**  
The cart is 2 feet wider on the combine side allowing the operator more room to navigate with a wider combine head.

*J&M Patented!  
You won't find the wide top on any other cart!*



# FLAMAN

# Avonlea



## AVAILABLE TRACK SYSTEMS

### STORM TRACKER SERIES

36" Wide X 146" long belt  
Up to 1500 bushel capacity

### STORM TRACKER LT SERIES

36" Wide X 116" long belt  
Up to 1150 bushel capacity

### STABILIZER SERIES

- MASSIVE 46" x 151" tracks up to 2350 bushel capacity
- 36" x 146" tracks up to 1500 bushel capacity
- Industry first rubber spring suspension
- Bogie front & back pivot 14" & side pivot 7"
- One bolt track alignment
- Self-tensioning tracks provide 13,000lbs of belt tension

Stabilizer Series Design



## FRONT CORNER, DRAG AUGER CARTS

Capacities: 1150 to 2350 bushels  
Same great cart, but now with a drag system!

- Gearbox driven drag, no belts, no chains!
- Wide top on larger models
- X-tended Reach Auger
- Smooth transition between horizontal and vertical augers reduces grain damage and increases unload efficiency



## SCALE SYSTEMS

J&M offers 3 point or 5 point scales on all of their carts.

Optional scale monitors available with:



1. Hands-on GT400 Monitor



2. Hands-on GT560 Smart Monitor



3. Cloud based wireless system (iFarm Smart Phone App)

## SPEED TENDERS

Models LC290, LC390, LC535

### Standard Features:

- Electric brakes on all axles
- Conveyor has 17'3" max height with 180 degree range of motion (max reach height varies with model)
- Conveyor can be swivelled around to convey material back into the tank
- Available in red, green, blue, or tan
- NEW Tru-Trak V-Belt Conveyor - extra long conveyor with V-Belt and skirting design keeps the belt centred, reducing seed damage and premature belt wear due to misalignment

### Optional deluxe wireless remote control operates:

- Conveyor lift and swing
- Starts/stops conveyor
- Bottom gates on tank
- Auto fill scale system
- Hydraulically swings conveyor

Optional flow valve allows you to control the rate of unload



The conveyor is connected to the trailer, not the wagon. Seed is weighed as it leaves the tank, not the conveyor.

Front mount engine makes servicing and refueling easy



**FLAMAN** [www.flaman.com](http://www.flaman.com)

In Alberta:  
Nisku 888-850-9579  
Lethbridge 888-280-4418  
Medicine Hat 888-683-9503

In Saskatchewan:  
Saskatoon 888-381-9697  
Southey 888-732-6187  
Prince Albert 866-730-5271

Yorkton 888-343-3842  
Moosomin 888-329-2441  
In Manitoba:  
Swan River 888-631-0390

**Avonlea** [www.avonleagroup.net](http://www.avonleagroup.net)

In Manitoba:  
Domain 1-888-736-2467  
Deloraine (204) 747-3318

Check Out Our Online Store:  
[www.avonleagroup.ca](http://www.avonleagroup.ca)

